



SYMBOL: **4933459155** MANUFACTURER: **Milwaukee** EAN: **4002395287109**



M18 ONESLSP-0 - ONE-KEY™ LED compact site light, 4400 lm, 18 V, with equipment, 4933459155

- Lumens 1000/2100/4400
- Max. run time with M18 B5 battery: 8/4/2 h
- Voltage: 18 V
- Self-centering metal hook
- Durable construction
- IP54 rating
- Bulb type: LED
- Battery type: Li-ion
- No. of batteries supplied 0
- Weight with battery pack: 5.4 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 669,00 zł~~ **-10%**

2 402,10 zł (tax excl.)

(2 954,58 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://imilwauke.pl/en/17732-m18-oneslsp-0-one-key-led-compact-site-light-4400-lm-18-v-with-equi...>

DESCRIPTION

- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Optimise brightness and run time by adjusting the light output between 0 - 4400 Lumens.
- Program automatic schedules to decide during which days/times the light is running.
- TRUEVIEW™ high definition lighting solutions combine the most advanced LED technology.
- 180° and 360° electronic light control for large area and task lighting.
- Self-centering metal hook designed for hanging the light from studs or pipes.
- Dual power source, powered by either M18™ REDLITHIUM™-ION battery packs or use of 2.5 m hardwired cord.
- AC outlet gives the possibility to string multiple lights together.
- Up to 8 hours of run time on low setting when powered by an M18™ REDLITHIUM™-ION 5.0 Ah battery pack.
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions.
- IP54 rating in battery mode - light is protected from dust and splashing water.
- Security cable included.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied without battery and charger.

FEATURES

Symbol	M18ONESLSP-0
Nazwa	lampa strefowa LED
Waga [kg]	5.40
Stopień ochrony IP	IP 54
Jasność	1000/2100/4400 lm

