



SYMBOL: **4933459431** MANUFACTURER: **Milwaukee** EAN: **4058546010928**



M18 ONERSAL-0 - ONE-KEY™ LED remote stand light, 5400 lm, 18 V, without equipment, 4933459431

- Lumens: 1550/3000/5400
- Max. run time with M18 B9 battery: 26/12.5/7 h
- Voltage: 18 V
- Impact resistant
- Reinforced leg design
- Height adjustment
- Compartment for 2 batteries
- IP67 rating
- Bulb type: LED
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 9.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~3 579,00 zł~~ **-10%**

3 221,10 zł (tax excl.)

(3 961,95 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://imilwauke.pl/en/17735-m18-onersal-0-one-key-led-remote-stand-light-5400-lm-18-v-without-e...>

DESCRIPTION

- Optimise brightness and run time by adjusting the light output from 0 - 5400 Lumens.
- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- IP67 allows use in all weather conditions (heavy rain, snow, dusty environments).
- Reinforced leg design with 3 different leg deployment options for best durability and stability.
- Highly durable and impact resistant polycarbonate lens and all aluminium cam design to protect the light from rough working conditions.
- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail.
- Sealed battery compartment for up to 2 packs to extend run time.
- Change height from 0.5 m to 1.65 m to cast light from overhead to limit shadows.
- Collapsible to only 55 cm for easy storage and transportation.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- **Supplied without battery and charger.**

FEATURES

| | |
|--------------------|-------------------|
| Symbol | M18ONERSAL |
| Nazwa | lampa stojąca LED |
| Waga [kg] | 9.10 |
| Stopień ochrony IP | IP 67 |
| Jasność | 1550/3000/5400 lm |