

















MANUFACTURER: Milwaukee EAN: 4002395003174



M18 BPD-402C - Compact percussion drill 18 V, 4.0 Ah, in case, with 2 batteries and charger, 4933443520

- · Voltage: 18 V
- No load speed gear 1/2: 0-450/0-1800 rpm
- Max. percussion rate: 0-28800 bpm
- Max. torque: 60 Nm
- · Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 38/13/16 mm
- Wood screws to: 7 mm
- · Battery type: Li-ion
- · No. of batteries supplied: 2
- Battery pack capacity: 4.0 Ah
- Charger supplied: 80 min
- Weight with battery pack: 2.1 kg





1 859,00 zł -10%

1 673,10 zł (tax excl.)

(2 057,91 zł (tax incl.))

Pay**U**i VISA MasterCard

link > https://imilwauke.pl/en/17776-m18-bpd-402c-compact-percussion-drill-18-v-40-ah-in-case-with-2-bat...

## DESCRIPTION

- Vibration drilling into concrete: 13 m/s²
- Vibration drilling into metal: 0.95 m/s²
   Vibration screw driving: 0.66 m/s²

- Sound pressure level: 84.7 dB(A)
- Compact percussion drill measuring only 198 mm in length, making it ideal for working in confined spaces.
   High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
   REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
   Full metal gear box delivers maximum performance and long life.

- 13 mm metal chuck for quick bit changes and bit retention
- 3 stage mode selector allows the user to switch between rotary, screw drive and percussion modes quickly and easily.
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- REDLITHIUM\*\*-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
  Flexible battery system: works with all MILWAUKEE® M18\*\* batteries.
- · Supplied in case (Kitbox) with 2 batteries and charger.

## FEATURES

Symbol	M18BPD-402C
Тур	udarowa
Nm max	60.00
Częstość udaru [ud/min]	0-28800
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	38.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-450/0-1800

