



SYMBOL: **4933464138** MANUFACTURER: **Milwaukee** EAN: **4058546220839**



## M12 FPDXXKIT-202X - Sub compact percussion drill with removable chucks 12 V, 2.0 Ah, with 2 batteries and charger, 4933464138

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 37 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 1.2 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



1 899,00 zł **-10%**

**1 709,10 zł** (tax excl.)

(2 102,19 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/17784-m12-fpdxxkit-202x-sub-compact-percussion-drill-with-removable-chucks...>

### DESCRIPTION

- High performance compact 6-in-1 percussion drill system for extreme versatility.
- Removable chuck system with 3 different heads for multiples of applications.
- Brushless POWERSTATE™ motor delivers up to 44 Nm of torque.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 13 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head.
- 1/4" hex drive behind chuck fitting, reduces drill length to 138 mm when required.
- Full metal planetary gearbox transmission for extreme durability.
- LED light for workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Standard equipment: removable chuck, offset attachment, right angle attachment.
- Supplied in case (HD Box) with 2 batteries and charger.

### FEATURES

|                                |                  |
|--------------------------------|------------------|
| Symbol                         | M12FPDXXKIT-202X |
| Typ                            | udarowa          |
| Nm max                         | 37.00            |
| Częstość udaru [ud/min]        | 0-25500          |
| Ilość akumulatorów             | 2                |
| Ilość biegów                   | 2                |
| Zasilanie                      | battery          |
| Napięcie akumulatora [V]       | 12               |
| Średnica uchwytu wiertarskiego | 13.00            |
| Średnica wiercenia w drewnie   | 35.00            |
| Średnica wiercenia w metalu    | 13.00            |
| Średnica wiercenia w murze     | 13.00            |
| Obroty [obr/min]               | 0-450/0-1700     |

