



SYMBOL: **4933464136** MANUFACTURER: **Milwaukee** EAN: **4058546220815**



M12 FPDx-202X - Sub compact percussion drill with removable chuck 12 V, 2.0 Ah, with 2 batteries and charger, 4933464136

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 37 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 1.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



1 579,00 zł **-10%**

1 421,10 zł (tax excl.)

(1 747,95 zł (tax incl.))



Product page

link > <https://imilwauke.pl/en/17785-m12-fpdx-202x-sub-compact-percussion-drill-with-removable-chuck-12-...>

DESCRIPTION

- High performance compact 6-in-1 percussion drill system for extreme versatility.
- Removable chuck system with 3 different heads for multiples of applications.
- Brushless POWERSTATE™ motor delivers up to 44 Nm of torque.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 13 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head.
- 1/4" hex drive behind chuck fitting, reduces drill length to 138 mm when required.
- Full metal planetary gearbox transmission for extreme durability.
- LED light for workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Standard equipment: removable chuck.
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M12FPDX-202X
Typ	udarowa
Nm max	37.00
Częstość udaru [ud/min]	0-25500
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	35.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	13.00
Obroty [obr/min]	0-450/0-1700

