



SYMBOL: **4933446045** MANUFACTURER: **Milwaukee** EAN: **4002395004652**



M12 BPD-202X - Sub compact percussion drill 12 V, 2.0 Ah, in case, with 2 batteries and charger, 4933446045

- Voltage: 12 V
- No load speed gear 1/2: 0-400/0-1500 rpm
- Max. percussion rate: 0-22500 bpm
- Max. torque: 30 Nm
- Chuck capacity: 10 mm
- Max. drilling wood/ metal/ masonry: 22/10/10 mm
- Wood screws to: 6 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 1.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 129,00 zł~~ **-10%**

1 016,10 zł (tax excl.)

(1 249,80 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://milwaukee.pl/en/17789-m12-bpd-202x-sub-compact-percussion-drill-12-v-20-ah-in-case-with-2...>

DESCRIPTION

- Vibration drilling into concrete: 7.9 m/s²
- Vibration drilling into metal: 1.5 m/s²
- Vibration screw driving: 0.4 m/s²
- Sound power level: 97 dB(A)
- Sound pressure level: 85 dB(A)
- High performance sub compact percussion drill measures 190 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 10 mm metal chuck for quick bit changes and bit retention.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M12BPD-202X
Typ	udarowa
Nm max	30.00
Częstość udaru [ud/min]	0-22500
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	10.00
Średnica wiercenia w drewnie	22.00
Średnica wiercenia w metalu	10.00
Średnica wiercenia w murze	10.00
Obroty [obr/min]	0-400/0-1500

