



SYMBOL: **4933441950** MANUFACTURER: **Milwaukee** EAN: **4002395002702**



## M12 BPD-0 - Sub compact percussion drill 12 V, without equipment, 4933441950

- Voltage: 12 V
- No load speed gear 1/2: 0-400/0-1500 rpm
- Max. percussion rate: 0-22500 bpm
- Max. torque: 30 Nm
- Chuck capacity: 10 mm
- Max. drilling wood/ metal/ masonry: 22/10/10 mm
- Wood screws to: 6 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.2/1.5 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



519,00 zł **-10%**

**467,10 zł** (tax excl.)

(574,53 zł (tax incl.))

PayU



Product page

link > <https://imilwauke.pl/en/17791-m12-bpd-0-sub-compact-percussion-drill-12-v-without-equipment-49334...>

### DESCRIPTION

- Vibration drilling into concrete: 7.9 m/s<sup>2</sup>
- Vibration drilling into metal: 1.5 m/s<sup>2</sup>
- Vibration screw driving: 0.4 m/s<sup>2</sup>
- Sound power level: 97 dB(A)
- Sound pressure level: 85 dB(A)
- High performance sub compact percussion drill measures 190 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 10 mm metal chuck for quick bit changes and bit retention.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied without battery and charger.

### FEATURES

Symbol	M12BPD-0
Typ	udarowa
Nm max	30.00
Częstość udaru [ud/min]	0-22500
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	10.00
Średnica wiercenia w drewnie	22.00
Średnica wiercenia w metalu	10.00
Średnica wiercenia w murze	10.00
Obroty [obr/min]	0-400/0-1500