



SYMBOL: **4933464131** MANUFACTURER: **Milwaukee** EAN: **4058546220761**



M12 FPD-402XA - Sub compact 2-speed percussion drill 12 V, 4.0 Ah, with 2 batteries and charger, 4933464131

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 44 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/metal/masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 4.0 Ah
- Weight with battery pack: 1.5 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/17794-m12-fpd-402xa-sub-compact-2-speed-percussion-drill-12-v-40-ah-with-...>

DESCRIPTION

- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 13 mm metal chuck for quick bit changes and bit retention.
- Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- Fuel gauge displays remaining charge.
- Bright LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

| | |
|--------------------------------|---------------|
| Symbol | M12 FPD-402XA |
| Typ | udarowa |
| Nm max | 44.00 |
| Częstość udaru [ud/min] | 0-25500 |
| Ilość akumulatorów | 2 |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 12 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 35.00 |
| Średnica wiercenia w metalu | 13.00 |
| Średnica wiercenia w murze | 13.00 |
| Obroty [obr/min] | 0-450/0-1700 |

