



SYMBOL: **4933459801** MANUFACTURER: **Milwaukee** EAN: **4058546029739**



M12 FPD-0 - Sub compact 2-speed percussion drill 12 V, FUEL™, without equipment

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 44 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.2/1.5 kg



Product page

link > <https://imilwauke.pl/en/17796-m12-fpd-0-sub-compact-2-speed-percussion-drill-12-v-fuel-without-eq...>



DESCRIPTION

- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 13 mm metal chuck for quick bit changes and bit retention.
- Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- Fuel gauge displays remaining charge.
- Bright LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied without battery and charger.

FEATURES

Symbol	M12FPD-0
Typ	udarowa
Nm max	44.00
Częstość udaru [ud/min]	0-25500
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	35.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	13.00
Obroty [obr/min]	0-450/0-1700