

PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



ne > Drill drivers > Drill drivers > Percussion drill-driv



SYMBOL: 4933464557 MANUFACTURER: Milwaukee FAN: 4058546225025 $\star \star \star \star \star$ M18 CBLPD-0X - Compact brushless percussion drill 18 V, in case, without equipment, 4933464557

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.

- Voltage: 18 V
- No load speed gear 1/2: 0-500/0-1800 rpm
- Max. percussion rate: 0-27000 bpm
- Max. torque: 60 Nm
- · Chuck capacity: 13 mm
- Speed settings: 2 • Max. drilling wood/ metal/ masonry: 52/13/16 mm



link > https://imilwauke.pl/en/17811-m18-cblpd-0x-compact-brushless-percussion-drill-18-v-in-case-withou...

DESCRIPTION

- No. of batteries supplied: 0
- Weight with battery pack: 1.5/1.8 kg

Compact brushless percussion drill measuring 165 mm in length for access into tight spaces

- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention.
 REDLINK[™] overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM *-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 60 Nm of torque best power to size ratio.

- All metal reversible belt clip to hang your tool quickly and easily.
 On board fuel gauge and LED light.
 Flexible battery system: works with all MILWAUKEE® M18st batteries.
- · Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18CBLPD-0X
Тур	udarowa
Nm max	60.00
Częstość udaru [ud/min]	0-27000
Ilość akumulatorów	brak
llość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	52.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-500/0-1800