





SYMBOL: **4933464266**

MANUFACTURER: Milwaukee

FAN: 4058546222116

M18 FDD2-0X - Drill driver 18 V, FUEL™, in case, without equipment

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products"

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- · Chuck capacity: 13 mm
- · Speed settings: 2
- · Max. drilling wood/ metal: 89/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.1 kg













Product page link > https://imilwauke.pl/en/17847-m18-fdd2-0x-drill-driver-18-v-fuel-in-case-without-equipment.html

DESCRIPTION

- · Higher power efficiency under load outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
 Advanced heavy duty chuck providing increased bit grip.

- Brushless POWERSTATE™ motor for heavy application under load.

 REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 Battery fuel gauge displays remaining charge.
- · 40 percent brighter LED workspace illumination vs previous model
- · All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- · Supplied in case (HD Box) without battery and charger.

FFATURES

| Symbol | M18FDD2-0X F |
|--------------------------------|--------------|
| Тур | bezudarowa |
| Nm max | 135.00 |
| Ilość akumulatorów | brak |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 89.00 |
| Średnica wiercenia w metalu | 16.00 |
| Obroty [obr/min] | 0-550/0-2000 |

