PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



e > Drill drivers > Drill drivers > Drill drivers without impact



SYMBOL: 4933464266 MANUFACTURER: Milwaukee FAN: 4058546222116 $\star \star \star \star \star$ M18 FDD2-0X - Drill driver 18 V, FUEL™, in case, without equipment, 4933464266

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal: 89/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.1 kg





link > https://imilwauke.pl/en/17847-m18-fdd2-0x-drill-driver-18-v-fuel-in-case-without-equipment-493346...

DESCRIPTION

Higher power efficiency under load - outstanding torque of 135 Nm.

Extremely compact design of 175 mm length for access into tight spaces.
 Advanced heavy duty chuck providing increased bit grip.

- Bushless POWERSTATE[™] motor for heavy application under load.
 REDLINK PLUS[™] intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM ~-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 Battery fuel gauge displays remaining charge.
- · 40 percent brighter LED workspace illumination vs previous model
- · All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries.
- · Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18FDD2-0XF
Тур	bezudarowa
Nm max	135.00
llość akumulatorów	brak
llość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Obroty [obr/min]	0-550/0-2000