



SYMBOL: **4933446198** MANUFACTURER: **Milwaukee** EAN: **4002395004867**



M18 BDD-402X - Compact drill driver, 18 V, 4.0 Ah, in case, with 2 batteries and charger, 4933446198

- Voltage: 18 V
- Max. torque: 60 Nm
- Max. drilling wood: 38 mm
- Max. drilling steel: 13 mm
- No load speed gear 1: 0 - 450 rpm
- No load speed gear 2: 0 - 1800 rpm
- Wood screws to: 7 mm
- Battery type: Li-ion
- Battery pack capacity: 4.0 Ah
- Weight with battery pack (M18 B4): 2 kg



~~1 889,00 zł~~ **-10%**

1 700,10 zł (tax excl.)

(2 091,12 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/17860-m18-bdd-402x-compact-drill-driver-18-v-40-ah-in-case-with-2-batteri...>

DESCRIPTION

- Compact drill driver measuring only 185 mm in length, making it ideal for working in confined spaces.
- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear box delivers maximum performance and long life.
- 13 mm metal chuck for quick bit changes and bit retention.
- 17 stage torque adjustment plus additional drilling for maximum flexibility.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Brightest LED workspace illumination.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

FEATURES

| | |
|--------------------------------|--------------|
| Symbol | M18BDD-402X |
| Typ | bezударowa |
| Nm max | 60.00 |
| Ilość akumulatorów | 2 |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 38.00 |
| Średnica wiercenia w metalu | 13.00 |
| Obroty [obr/min] | 0-450/0-1800 |

