



SYMBOL: **4933451380** MANUFACTURER: **Milwaukee** EAN: **4002395160587**



**M18 CHPX-502X - High performance SDS-Plus hammer 18 V, 5.0 Ah, FUEL™, in HD Box, with 2 batteries and charger, 4933451380**

**NOTE: The product has been withdrawn from sale by the manufacturer. No suggested replacements available.**

- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism delivers 4.0 J (EPTA) of impact energy at low 8.6 m/s<sup>2</sup> vibrations thanks to the new dual rail anti-vibration system
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.



Product page

link > <https://imilwauke.pl/en/17962-m18-chpx-502x-high-performance-sds-plus-hammer-18-v-50-ah-fuel-in-h...>



## DESCRIPTION

Vibration chiseling/drilling: 7.1/8.6 m/s<sup>2</sup>

Sound power level: 102.1 dB(A)

Sound pressure level: 91.1 dB(A)

FIXTEC system - keyless chuck changing.

Fuel gauge displays remaining charge.

Milwaukee® designed and built brushless POWERSTATE™ motor

REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life

High powered motor gives corded tool performance

REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.

All metal gear case - optimum seating of the gears for enhanced service life

Individual battery cell monitoring optimises tool run time and ensures long term pack durability

Compatible with M18-28 CPDEX dust extractor

Flexible battery system: works with all Milwaukee® M18™ batteries

## FEATURES

Symbol	M18CHPX-502X
Waga [kg]	4.30
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000
Energia uderu	4.00
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350