



SYMBOL: **4933451431** MANUFACTURER: **Milwaukee** EAN: **4002395163304**



## M18 CHPX-0X - High performance SDS-Plus hammer 18 V, FUEL™, in HD Box, without equipment, 4933451431

**NOTE: The product has been withdrawn from sale by the manufacturer. No suggested replacements available.**

- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism delivers 4.0 J (EPTA) of impact energy at low 8.6 m/s<sup>2</sup> vibrations thanks to the new dual rail anti-vibration system
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility



Product page

link > <https://imilwauke.pl/en/17965-m18-chpx-0x-high-performance-sds-plus-hammer-18-v-fuel-in-hd-box-wi...>



### DESCRIPTION

- Vibration chiseling/drilling: 7.1/8.6 m/s<sup>2</sup>
- Sound power level: 102.1 dB(A)
- Sound pressure level: 91.1 dB(A)
- Fuel gauge displays remaining charge.
- FIXTEC system - keyless chuck changing.
- Milwaukee® designed and built brushless POWERSTATE™ motor.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- High powered motor gives corded tool performance.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- All metal gear case - optimum seating of the gears for enhanced service life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Compatible with M18-28 CPDEX dust extractor.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

### FEATURES

Symbol	M18CHPX-0X
Waga [kg]	3.60
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000
Energia uderu	4.00
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350