



SYMBOL: **4933451430** MANUFACTURER: **Milwaukee** EAN: **4002395162697**



M18 CHX-0 - SDS-Plus hammer 18 V, FUEL™, in case, without equipment, 4933451430

- Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5J of impact energy at low 8.9m/s² vibrations.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- FIXTEC system - keyless chuck changing.

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/17972-m18-chx-0-sds-plus-hammer-18-v-fuel-in-case-without-equipment-49334...>



DESCRIPTION

Vibration chiseling/drilling: 9.5/8.9 m/s²

Sound power level: 101.7 dB(A)

Sound pressure level: 90.7 dB(A)

REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load

REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life

Compact, ergonomic design for increased end user comfort

All metal gear case - optimum seating of the gears for enhanced service life

Individual battery cell monitoring optimises tool run time and ensures long term pack durability

Fuel gauge displays remaining charge

Compatible with M18 CDEX dust extractor

Flexible battery system: works with all Milwaukee® M18™ batteries

FEATURES

Symbol	M18CHX-0X
Waga [kg]	2.80
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5100
Energia uderu	2.50
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1400

