



SYMBOL: **4933446049** MANUFACTURER: **Milwaukee** EAN: **4002395004676**



M12 CH-402X - Sub compact SDS-Plus hammer 12 V, 4.0 Ah, FUEL, in HD Box, with 2 batteries and charger, 4933446049

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm.
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day.
- Will drill over 60 50 mm x 6 mm holes per battery charge.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.
- 2Optimised hammer drilling up to 6 - 10 mm (max 13 mm).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 119,00 zł~~ **-10%**

1 907,10 zł (tax excl.)

(2 345,73 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/17982-m12-ch-402x-sub-compact-sds-plus-hammer-12-v-40-ah-fuel-in-hd-box-w...>

DESCRIPTION

Vibration drilling: 4.4 m/s²

Sound power level: 95.5 dB(A)

Sound pressure level: 84.5 dB(A)

Superior power to weight ratio in its class with Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time

REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load

REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life

43 mm neck size - compatible with M12 DE dust extractor

Flexible battery system: works with all Milwaukee® M12™ batteries

FEATURES

Symbol	M12CH-402X
Waga [kg]	1.90
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-6575
Energia uderu	1.10
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica wiercenia w betonie	13.00
Średnica wiercenia w drewnie	13.00
Średnica wiercenia w metalu	10.00
Obroty [obr/min]	0-900