



SYMBOL: **4933464091** MANUFACTURER: **Milwaukee** EAN: **4058546220365**



## M18 ONEID2-502X - 1/4" HEX impact driver 18 V, FUEL™ ONE-KEY™, in case, with 2 batteries and charger, 4933464091

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
- Max. bolt diameter: M16
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 1.7 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page

link > <https://imilwauke.pl/en/20002-m18-oneid2-502x-14-hex-impact-driver-18-v-fuel-one-key-in-case-with...>

### DESCRIPTION

- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- Connect via Bluetooth® with the ONE-KEY™ app.
- ONE-KEY™ app provides inventory function for total management of your complete tool/equipment fleet.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Control speed, torque, start and end speeds and LED.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Standard equipment: belt clip and bit holder.
- **Supplied in case (HD Box) with 2 batteries and charger.**

### FEATURES

Symbol	M18ONEID2-502X
Wyjście	1/4"
Nm max	119/176/226/0-226
Częstość uderu [ud/min]	1200/3400/4300/0-4300
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1900/2800/3600/0-3600

