



SYMBOL: **4933464799** MANUFACTURER: **Milwaukee** EAN: **4058546227449**



M18 FBJS-0X - Body grip jigsaw 18 V, FUEL™, in case without equipment, 4933464799

- Voltage: 18 V
- Stroke length: 25 mm
- No load stroke rate: 800 - 3500 spm
- Max. cutting capacity wood/steel/aluminium: 100/10/19 mm
- Bevel capacity: 45°
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.8 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



1 849,00 zł **-17%**

1 534,67 zł (tax excl.)

(1 887,64 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/20024-m18-fbjs-0x-body-grip-jigsaw-18-v-fuel-in-case-without-equipment-49...>

DESCRIPTION

- Brushless POWERSTATE™ motor for fast cutting, long tool life and up to 32 m in 19 mm OSB (on a 5.0 Ah pack).
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Patented FIXTEC™ blade clamp for fast and easy blade change.
- 5 stage pendulum action for increased cutting performance.
- Ambidextrous on / off switch allows user to turn the tool on in any position.
- 6-speed settings with auto controlled start mode allows the tool to start slow and ramp up to full speed when load is detected for smooth and accurate cut starts.
- 3500 SPM delivers smooth cuts, minimised chipping and vibration.
- Dust blower keeps the cut line free of wood dust.
- Integrated LED light for workspace illumination.
- Detachable soft shoe avoids marks and scratches when cutting soft materials.
- Supplied with 1 x blade, dust extraction adapter, dust cover, splinter guard, soft shoe.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18FBJS-0X
Długość skoku	25.00
Ilość akumulatorów	brak
Ilość suwów	800-3500
Zasilanie	battery
Napięcie akumulatora [V]	18