



SYMBOL: **4933464516** MANUFACTURER: **Milwaukee** EAN: **4058546224615**



M18 BLPD2-0X - Brushless percussion drill 18 V, in case, without equipment, 4933464516

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-1800 rpm
- Max. percussion rate: 0-28800 bpm
- Max. torque: 82 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal/ masonry: 76/13/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 189,00 zł~~ **-34%**

782,98 zł (tax excl.)

(963,07 zł (tax incl.))



Product page

link > <https://imilwauke.pl/en/20058-m18-blpd2-0x-brushless-percussion-drill-18-v-in-case-without-equipm...>

DESCRIPTION

- New brushless motor design delivers 40 % more torque than previous model - up to 82 Nm.
- Compact design (180 mm in length) provides excellent balance and control, ideal for overhead applications or work in tight spaces.
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Optimised speed for faster drilling & fastening (0-550/ 0-1800 rpm).
- On board fuel gauge and LED light.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18BLPD2-0X
Typ	udarowa
Nm max	82.00
Częstość udaru [ud/min]	0-28800
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	76.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-550/0-1800

