



SYMBOL: **4933471282** MANUFACTURER: **Milwaukee** EAN: **4058546289102**



## M18 FDD2-503X - Drill driver 18 V, 5.0 Ah, FUEL™, in case, with 3 batteries and charger

**NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.**

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal: 89/16 mm



Product page link > <https://imilwauke.pl/en/20073-m18-fdd2-503x-drill-driver-18-v-50-ah-fuel-in-case-with-3-batteries...>



### DESCRIPTION

- Battery type: Li-ion
- No. of batteries supplied: 3
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 2.1 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 3 batteries and charger.**

### FEATURES

Symbol	M18FDD2-503X
Typ	bezударowa
Nm max	135.00
Ilość akumulatorów	3
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Obroty [obr/min]	0-550/0-2000