



SYMBOL: **4933431558** MANUFACTURER: **Milwaukee** EAN: **4002395242771**



## HD18 HX-0C - 4 -Mode SDS-Plus hammer 18 V, HEAVY DUTY, in case, without equipment, 4933431558

- Voltage: 18 V
- No load speed: 1400 rpm
- Max. percussion rate: 4200 bpm
- Blow energy: 2.4 J
- Tool holder: SDS-Plus
- Max. drilling wood/ metal/ concrete: 30/13/24 mm
- Optimised drilling capacity in concrete:  $\varnothing$  6 - 18 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight: 3 kg
- Weight with battery pack: 3.7 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page

link > <https://imilwauke.pl/en/20081-hd18-hx-0c-4-mode-sds-plus-hammer-18-v-heavy-duty-in-case-without-e...>



### DESCRIPTION

- Vibration drilling and chiseling: 12.2/7.4 m/s<sup>2</sup>
- Sound power level: 99 dB(A)
- Sound pressure level: 88 dB(A)
- High powered motor gives corded tool performance
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.
- All metal gear case: optimum seating for gears to enhance service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Variolock and hammer stop function.
- FIXTEC™ system - keyless chuck changing.
- Mechanical clutch: protects tool when bit binds up.
- Anti-Vibration-System delivers max. comfort by minimising vibration.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Supplied in case (Kitbox) without battery and charger.

### FEATURES

Symbol	HD18HX-0C
Waga [kg]	3.00
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	4200
Energia uderu	2.40
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	24.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	1400

