



SYMBOL: **4933451029** MANUFACTURER: **Milwaukee** EAN: **4002395136933**



M28 CHPX-0X - 4-Mode SDS-Plus hammer 28 V, FUEL™, in case without equipment, 4933451029

- Voltage: 28 V
- No load speed: 0-1350 rpm
- Max. percussion rate: 0-5000 bpm
- Blow energy: 4.1 J
- Tool holder: SDS-Plus
- Max. drilling wood/ steel/ concrete: 30/13/28 mm
- Optimised drilling capacity in concrete: \varnothing 7 - 24 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 4.7 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/20083-m28-chpx-0x-4-mode-sds-plus-hammer-28-v-fuel-in-case-without-equipm...>

DESCRIPTION

- Vibration chiseling and drilling: 8.1 m/s²
- Sound power level: 103.7 dB(A)
- Sound pressure level: 92.7 dB(A)
- Brushless POWERSTATE™ motor.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- High powered motor gives corded tool performance.
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s² vibrations thanks to the new dual rail anti-vibration system.
- All metal gear case - optimum seating of the gears for enhanced service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- FIXTEC™ system - keyless chuck changing.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining battery charge.
- Compatible with M18-28 CPDEX dust extractor.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M28CHPX-0X
Waga [kg]	3.70
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000
Energia uderu	4.10
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	28
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350

