



SYMBOL: **4933448015** MANUFACTURER: **Milwaukee** EAN: **4002395006779**



## M28 CHPXDE-502C - 4-Mode SDS-Plus hammer with dedicated dust extractor 28 V, 5.0 Ah, HEAVY DUTY, in case, 4933448015

- Set contains:
  - [M28 CHPX](#) - SDS-Plus hammer 28 V, FUEL™
  - [M18-28 CPDEX](#) - dust extractor M18-28 FUEL™ HEAVY DUTY
  - [M28 B5](#) - 2 batteries 5.0 Ah
  - [M28 C](#) - charger 90 min
- Supplied in case (Kitbox)

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page  
link > <https://imilwauke.pl/en/20084-m28-chpxde-502c-4-mode-sds-plus-hammer-with-dedicated-dust-extracto...>



### DESCRIPTION

- M28 CHPX:**  
TECHNICAL DATA:
- No load speed: 0-1350 rpm
  - Max. percussion rate: 0-5000 bpm
  - Blow energy: 4.1 J
  - Tool holder: SDS-Plus
  - Max. drilling wood/ steel/ concrete: 30/13/28 mm
  - Optimised drilling capacity in concrete:  $\phi$  7 - 24 mm
  - Vibration chiseling and drilling: 8.1 m/s<sup>2</sup>
  - Sound power level: 103.7 dB(A)
  - Sound pressure level: 92.7 dB(A)
  - Weight with battery pack: 4.7 kg

- DESCRIPTION:
- Brushless POWERSTATE™ motor.
  - REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
  - REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
  - High powered motor gives corded tool performance.
  - Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s<sup>2</sup> vibrations thanks to the new dual rail anti-vibration system.
  - All metal gear case - optimum seating of the gears for enhanced service life.
  - 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
  - FIXTEC™ system - keyless chuck changing.
  - Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
  - Fuel gauge displays remaining battery charge.
  - Compatible with M18-28 CPDEX dust extractor.

- M18-28 CPDEX:**  
TECHNICAL DATA:
- Max. drill bit diameter: 16 mm
  - Max. drilling depth: 90 mm
  - Max. drill bit length: 160 mm
  - Stroke length: 100 mm
  - Weight with battery pack: 1.6 kg

- DESCRIPTION:
- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch.
  - HEPA filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%.
  - Large dust collection box.
  - Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth.
  - Compatible with M18 CHPX & M28 CHPX.

### FEATURES

Symbol	M28CHPXDE-502C
Waga [kg]	6.30
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000



Energia udaru	4.10
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	28
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350

