



SYMBOL: **4933448015** MANUFACTURER: **Milwaukee** EAN: **4002395006779**



M28 CHPXDE-502C - 4-Mode SDS-Plus hammer with dedicated dust extractor 28 V, 5.0 Ah, HEAVY DUTY, in case, 4933448015

- Set contains:
 - [M28 CHPX](#) - SDS-Plus hammer 28 V, FUEL™
 - [M18-28 CPDEX](#) - dust extractor M18-28 FUEL™ HEAVY DUTY
 - [M28 B5](#) - 2 batteries 5.0 Ah
 - [M28 C](#) - charger 90 min
- Supplied in case (Kitbox)

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page link > <https://imilwauke.pl/en/20084-m28-chpxde-502c-4-mode-sds-plus-hammer-with-dedicated-dust-extracto...>



DESCRIPTION

- M28 CHPX:**
TECHNICAL DATA:
- No load speed: 0-1350 rpm
 - Max. percussion rate: 0-5000 bpm
 - Blow energy: 4.1 J
 - Tool holder: SDS-Plus
 - Max. drilling wood/ steel/ concrete: 30/13/28 mm
 - Optimised drilling capacity in concrete: ϕ 7 - 24 mm
 - Vibration chiseling and drilling: 8.1 m/s²
 - Sound power level: 103.7 dB(A)
 - Sound pressure level: 92.7 dB(A)
 - Weight with battery pack: 4.7 kg

- DESCRIPTION:
- Brushless POWERSTATE™ motor.
 - REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
 - REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 - High powered motor gives corded tool performance.
 - Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s² vibrations thanks to the new dual rail anti-vibration system.
 - All metal gear case - optimum seating of the gears for enhanced service life.
 - 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
 - FIXTEC™ system - keyless chuck changing.
 - Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 - Fuel gauge displays remaining battery charge.
 - Compatible with M18-28 CPDEX dust extractor.

- M18-28 CPDEX:**
TECHNICAL DATA:
- Max. drill bit diameter: 16 mm
 - Max. drilling depth: 90 mm
 - Max. drill bit length: 160 mm
 - Stroke length: 100 mm
 - Weight with battery pack: 1.6 kg

- DESCRIPTION:
- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch.
 - HEPA filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%.
 - Large dust collection box.
 - Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth.
 - Compatible with M18 CHPX & M28 CHPX.

FEATURES

Symbol	M28CHPXDE-502C
Waga [kg]	6.30
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000



Energia udaru	4.10
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	28
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350

