



SYMBOL: **4933464087** MANUFACTURER: **Milwaukee** EAN: **4058546220327**



## M18 FID2-0X - 1/4" HEX impact driver 18 V, FUEL™, in case, without equipment

**NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.**

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
- Max. bolt diameter: M16



Product page

link > <https://imilwauke.pl/en/20101-m18-fid2-0x-14-hex-impact-driver-18-v-fuel-in-case-without-equipmen...>



### DESCRIPTION

- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.7 kg
- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: belt clip and bit holder.
- Supplied in case (HD Box) without battery and charger.

### FEATURES

Symbol	M18FID2-0X
Wyjście	1/4"
Nm max	119/176/226/0-226
Częstość uderu [ud/min]	1200/3400/4300/0-4300
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1900/2800/3600/0-3600