





SYMBOL: 4933459187

MANUFACTURER: Milwaukee EAN: 4002395289226

M18 FQID-0X - 1/4" HEX impact driver 18 V, FUEL™ SURGE, in case, without equipment, 4933459187

- · Voltage: 18 V
- Impact rate: 1800/2900/4000/4000 ipm
- No load speed: 900/2100/3000/3000 rpm
- Max. torque: 50 Nm
- Max. bolt diameter: M14
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.7 kg

■ WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



1 559,00 zł -10%

1 403,10 zł (tax excl.)

(1 725,81 zł (tax incl.))



Pay**U** VISA MasterCard











link > https://imilwauke.pl/en/20104-m18-fqid-0x-14-hex-impact-driver-18-v-fuel-surge-in-case-without-eq..

DESCRIPTION

- Sound pressure level: 87.9 dB(A)
- Sound power level measured: 98.9 dB(A)
 The M18 FUEL™ SURGE™ 1/4* Hex hydraulic driver is Milwaukee Tool's quietest impact driver
- FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance and increased durability over a standard impact.
- · Delivers same performance in wood fastening as standard brushless impact drivers.
- POWERSTATE™ brushless motor delivers up to 0 3.000 rpm with constant power output to drive screws faster
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Self-tapping screw mode is designed to reduce walking when starting self-tapping screws as well as reduce overdriving, breaking and stripping out screws.

 REDLITHIUM**-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- $\cdot \text{Individual battery cell monitoring optimises tool run time and ensures long term pack durability } \\$
- •1/4" Hex chuck for quick and easy bit change.
- On board fuel gauge and LED light.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- · Supplied in case without battery and charger.

FEATURES

Symbol	M18FQID-0X
Wyjście	1/4"
Nm max	50
Częstość udaru [ud/min]	1800/2900/4000/4000
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	900/2100/3000/3000