

## PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



> Impact wrenches, impact drivers > Impact drivers



SYMBOL: 4933464090 MANUFACTURER: Milwaukee EAN: 4058546220358  $\star \star \star \star \star$ M18 ONEID2-0X - 1/4" HEX impact driver 18 V, FUEL™ ONE-KEY™, in case, without equipment, 4933464090

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torgue: 226 Nm
- Max. bolt diameter: M16



link > https://imilwauke.pl/en/20107-m18-oneid2-0x-14-hex-impact-driver-18-v-fuel-one-key-in-case-withou...



## DESCRIPTION

- No. of batteries supplied: 0
   Weight with battery pack: 1.7 kg
- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load outstanding torque of 226 Nm.

- Faster driving speed vs. previous model up to 3600 rpm and 4300 ipm.
  Extremely compact design total length of just 117 mm for access into tight spaces.
  Connect via Bluetooth® with the ONE-KEY™ app.
  ONE-KEY™ app provides inventory function for total management of your complete tool/equipment fleet.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
   Configure to any application choosing optimum tool settings for repeatable precision.
   Control speed, torque, start and end speeds and LED.

- Flexible battery system: works with all MILWAUKEE® M18<sup>™</sup> batteries.
   Standard equipment: belt clip and bit holder.
- · Supplied in case (HD Box) without battery and charger.

## FEATURES

Symbol	M180NEID2-0X
Wyjście	1/4"
Nm max	119/176/226/0-226
Częstość udaru [ud/min]	1200/3400/4300/0-4300
llość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1900/2800/3600/0-3600