



SYMBOL: **4933441960** MANUFACTURER: **Milwaukee** EAN: **4002395002696**

★★★★★

M12 BID-202C - Sub compact 1/4" HEX impact driver 12 V, 2.0 Ah, FUEL™, in case, with 2 batteries and charger

- Voltage: 12 V
- Impact rate: 0-3300 ipm
- No load speed: 0-2500 rpm
- Max. torque: 112 Nm
- Vibration screw driving: 12.9 m/s²
- Sound power level: 108 dB(A)
- Sound pressure level: 97 dB(A)
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 049,00 zł~~ **-10%**

944,10 zł (tax excl.)

(1 161,24 zł (tax incl.))

PayU **VISA** **MasterCard**

Product page

link > <https://imilwauke.pl/en/20110-m12-bid-202c-sub-compact-14-hex-impact-driver-12-v-20-ah-fuel-in-ca...>

DESCRIPTION

- High performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- 1/4" Hex chuck for quick and easy bit change.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied in case (Kitbox) with 2 batteries and charger.

FEATURES

Symbol	M12BID-202C
Wyjście	1/4"
Nm max	112
Częstość uderu [ud/min]	0-3300
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-2500