



SYMBOL: **4933459695** MANUFACTURER: **Milwaukee** EAN: **4058546028671**



M18 FHIWF12-0X - 1/2" Impact wrench, 1356 Nm, 18 V, FUEL™, in case, without equipment, 4933459695

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.

- Voltage: 18 V
- Max. torque: 130/400/1356/1356 Nm
- Nut-busting torque: 1898 Nm
- Impact rate: 0-950/0-1750/0-2100/0-2100 ipm
- No load speed: 0-550/0-1400/0-1750/0-1750 rpm
- Max. bolt diameter: M33
- Tool holder: 1/2" square



Product page

link > <https://imilwauke.pl/en/20115-m18-fhiwf12-0x-12-impact-wrench-1356-nm-18-v-fuel-in-case-without-e...>

DESCRIPTION

- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 3.3 kg
- Sound power level measured: 103.1 dB(A)
- Sound pressure level: 92.1 dB(A)
- The M18 FUEL™ high torque impact wrench delivers 1356 Nm fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides maximum nut-busting of 1898 Nm then shifts to 750 rpm for outstanding control when removing fasteners.
- 1/2" friction ring reception.
- New LED light is 40 percent brighter than previous model.
- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life.
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Supplied in case (HD Box) without battery and charger.

FEATURES

| | |
|--------------------------|--------------------|
| Symbol | M18FHIWF12-0X |
| Wyjście | 1/2" |
| Nm max | 1356 |
| Częstość uderu [ud/min] | 950/1750/2100/2100 |
| Ilość akumulatorów | brak |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Obroty [obr/min] | 550/1400/1750/1750 |

