



SYMBOL: **4933451071** MANUFACTURER: **Milwaukee** EAN: **4002395810550**



M18 FIWF12-502X - 1/2" Impact wrench, 300 Nm, 18 V, 5.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933451071

- Voltage: 18 V
- Max. torque: 40/120/300/120 Nm
- Impact rate: 2400/2600/3100/2600 ipm
- No load speed: 1700/2000/2500/2000 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 1.8 kg



Product page

link > <https://imilwauke.pl/en/20121-m18-fiwf12-502x-12-impact-wrench-300-nm-18-v-50-ah-fuel-in-case-wit...>



DESCRIPTION

- Sound power level measured: 104.5 dB(A)
- Sound pressure level: 93.5 dB(A)
- Brushless POWERSTATE™ motor for longer motor life and up to 20% more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials.
- 1/2" friction ring reception.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- All metal reversible belt clip – quickly and easily hang tool.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

| | |
|--------------------------|---------------------|
| Symbol | M18FIWF12-502X |
| Wyjście | 1/2" |
| Nm max | 300 |
| Częstość uderu [ud/min] | 2400/2600/3100/2600 |
| Ilość akumulatorów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Obroty [obr/min] | 1700/2000/2500/2000 |

