



SYMBOL: **4933459730** MANUFACTURER: **Milwaukee** EAN: **4058546029029**



M18 ONEFHIWF34-502X - 3/4" Impact wrench, 1627 Nm, 18 V, 5.0 Ah, ONE-KEY™, in case, with 2 batteries and charger, 4933459730

- Voltage: 18 V
- Max. torque: 702/1138/1627/1627 Nm
- Nut-busting torque: 2034 Nm
- Impact rate: 0-850/0-1850/0-2400/0-2400 ipm
- No load speed: 0-800/0-1300/0-1800/0-1800 rpm
- Max. bolt diameter: M33
- Tool holder: 3/4" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 3.5 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~3 489,00 zł~~ **-10%**

3 140,10 zł (tax excl.)

(3 862,32 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://imilwauke.pl/en/20133-m18-onefhiwf34-502x-34-impact-wrench-1627-nm-18-v-50-ah-one-key-in-...>

DESCRIPTION

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- The 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 2034 Nm then shifts to 750 rpm for outstanding control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 3/4" friction ring reception.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M18ONEFHIWF34-502X
Wyjście	3/4"
Nm max	1627
Częstość uderu [ud/min]	850/1850/2400/2400
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	800/1300/1800/1800

