PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



MANUFACTURER: Milwaukee EAN: 4002395160525 SYMBOL: 4933451374 $\star \star \star \star \star$ M18 ONEIWF12-502X - 1/2" Impact wrench, 300 Nm, 18 V, 5.0 Milwaukee Ah, ONE-KEY™, in case, with 2 batteries and charger, 4933451374 Voltage: 18 V • Max. torque: 40/120/220/300 Nm • Impact rate: 1300/2100/2550/3200 ipm • No load speed: 900/1400/1900/2500 rpm Tool holder: 1/2" square Battery type: Li-ion • No. of batteries supplied: 2 Battery pack capacity: 5.0 Ah Charger supplied: 59 min • Weight with battery pack: 1.8 kg Milwaukee 0 **U** WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION) 2 959,00 zł -10% 2 663,10 zł (tax excl.) 11 1 (3 275,61 zł (tax incl.)) PayU^{*} VISA MasterCard

link > https://imilwauke.pl/en/20138-m18-oneiwf12-502x-12-impact-wrench-300-nm-18-v-50-ah-one-key-in-cas...

DESCRIPTION

- Sound power level measured: 104.5 dB(A)
- Sound pressure level: 93.5 dB(A)
 M18 FIWF12 but with ONE-KEY[™] technology.

Impact wrenches, impact drivers > Impact wrenches

- Connect via Bluetooth® with the ONE-KEY™ app.
 Complete tool customisation via ONE-KEY™ app to tune the tool to your needs.
- Control speed, torque, start and end speeds and LED.
- Configure to any application choosing optimum tool settings for repeatable precision.
 Program/save profiles for unmatched control.
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull.
 Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
- ONE-KEY™ app also provides inventory function for total management of your complete tool/equipment fleet.
- Standard equipment: belt clip.
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries.
- · Supplied in case with 2 batteries and charger.

FEATURES

Symbol	M180NEIWF12-502X
Wyjście	1/2"
Nm max	300
Częstość udaru [ud/min]	1300/2100/2550/3200
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	900/1400/1900/2500