



PARTNER W DOBORZE ROZWIĄZAŃ
TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



Home > Impact wrenches, impact drivers > Impact wrenches



SYMBOL: **4933447134** MANUFACTURER: **Milwaukee** EAN: **4002395006014**

★★★★★

M12 BIW12-0 - Sub compact 1/2" impact wrench, 138 Nm, 12 V, without equipment

- Voltage: 12 V
- Max. torque: 138 Nm
- Impact rate: 0-3400 ipm
- No load speed: 0-2550 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~639,00 zł~~ **-10%**

575,10 zł (tax excl.)

(707,37 zł (tax incl.))

PayU  

Product page

link > <https://milwauke.pl/en/20142-m12-biw12-0-sub-compact-12-impact-wrench-138-nm-12-v-without-equipm...>

DESCRIPTION

- Vibration screw driving: 11.2 m/s²
- Sound power level: 109 dB(A)
- Sound pressure level: 98 dB(A)
- High performance sub compact impact wrench measures 171 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- 1/2" square drive with pin detent for use with universal sockets.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied without battery and charger.

FEATURES

Symbol	M12BIW12-0
Wyjście	1/2"
Nm max	138
Częstość uderu [ud/min]	0-3400
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-2550

