





## DESCRIPTION

- Vibration screw driving: 12.9 m/s<sup>2</sup>
- Sound power level: 108 dB(A)
  Sound pressure level: 97 dB(A)
- High performance sub compact impact wrench measures 165 mm in length making it ideal for working within confined spaces.
  REDLINK<sup>™</sup> overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- · 3/8" square drive with friction ring for use with universal sockets.

Impact wrenches, impact drivers > Impact wrenches

- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
  On board fuel gauge and LED light added user convenience and illumination in low lit working conditions.
- REDLITHIUM<sup>®</sup>-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life. Flexible battery system: works with all MILWAUKEE® M12<sup>®</sup> batteries.

## · Supplied without battery and charger.

## FEATURES

Symbol	M12BIW38-0
Wyjście	3/8"
Nm max	135
Częstość udaru [ud/min]	0-3300
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-2500

