



SYMBOL: **4933464611** MANUFACTURER: **Milwaukee** EAN: **4058546225568**



## M12 FIW14-0 - Sub compact 1/4" impact wrench, 12 V, without equipment, 4933464611

- Voltage: 12 V
- Max. torque: 136 Nm
- Impact rate: 1300/2000/4300 ipm
- No load speed: 1300/1900/3200/3200 rpm
- Max. bolt diameter: M12
- Tool holder: 1/4" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 0.9 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~889,00 zł~~ **-10%**

**800,10 zł** (tax excl.)

(984,12 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/20145-m12-fiw14-0-sub-compact-14-impact-wrench-12-v-without-equipment-493...>

### DESCRIPTION

- Sound power level measured: 102.86 dB(A)
- Sound pressure level: 91.86 dB(A)
- More power, more compact, more control.
- Up to 115 Nm of maximum fastening torque.
- Up to 136 Nm of maximum nut busting torque.
- 1/4 anvil with friction ring for quick and easy socket changes.
- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Better access in tight spaces with an overall length of only 129.5 mm.
- 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise control.
- Bright LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Supplied without battery and charger.

### FEATURES

Symbol	M12FIW14-0
Wyjście	1/4"
Nm max	136
Częstość uderu [ud/min]	1300/2000/4300
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	1300/1900/3200/3200

