



SYMBOL: **4933416930** MANUFACTURER: **Milwaukee** EAN: **4002395237739**



HD28 IW-0 - 1/2" Impact wrench, 440 Nm, 28 V, HEAVY DUTY, without equipment

- Voltage: 28 V
- Max. torque: 440 Nm
- Impact rate: 0-2450 ipm
- No load speed: 0-1450 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 4.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page
link > <https://imilwauke.pl/en/20150-hd28-iw-0-12-impact-wrench-440-nm-28-v-heavy-duty-without-equipment...>

DESCRIPTION

- Vibration screw driving: 11.3 m/s²
- Sound power level: 91 dB(A)
- Sound pressure level: 80 dB(A)
- With its 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Durable, lightweight magnesium gear case for extended life and comfort.
- Variable speed trigger for enhanced control and accuracy.
- 1/2" square drive with detent pin for secure socket retention.
- Non-slip gripping surfaces for maximum comfort and control.
- Exclusive reversible battery pack design for optimal tool balance.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Supplied without battery and charger.

FEATURES

| | |
|--------------------------|----------|
| Symbol | HD28IW-0 |
| Wyjście | 1/2" |
| Nm max | 440 |
| Częstość uderu [ud/min] | 0-2450 |
| Ilość akumulatorów | brak |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 28 |
| Obroty [obr/min] | 0-1450 |