PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



Impact wrenches, impact drivers > Impact wrenches





## DESCRIPTION

- Vibration screw driving: 11.3 m/s<sup>2</sup>
- Sound pressure level: 80 dB(A)
- With its 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Durable, lightweight magnesium gear case for extended life and comfort.
  Variable speed trigger for enhanced control and accuracy.
- 1/2" square drive with detent pin for secure socket retention
- · Non-slip gripping surfaces for maximum comfort and control.
- Exclusive reversible battery pack design for optimal tool balance
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
  Fuel gauge displays remaining charge.
- REDULTHIUM\*-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

· Supplied in case with 2 batteries and charger.

## FEATURES

Symbol	HD28IW-32C
Wyjście	1/2"
Nm max	440
Częstość udaru [ud/min]	0-2450
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	28
Obroty [obr/min]	0-1450