



SYMBOL: **4933416920** MANUFACTURER: **Milwaukee** EAN: **4002395237715**



HD28 IW-32C - 1/2" Impact wrench, 440 Nm, 28 V, HEAVY DUTY, in case, with 2 batteries and charger

- Voltage: 28 V
- Max. torque: 440 Nm
- Impact rate: 0-2450 ipm
- No load speed: 0-1450 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 3.0 Ah
- Charger supplied: 60 min
- Weight with battery pack: 4.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/20152-hd28-iw-32c-12-impact-wrench-440-nm-28-v-heavy-duty-in-case-with-2-...>



DESCRIPTION

- Vibration screw driving: 11.3 m/s²
- Sound power level: 91 dB(A)
- Sound pressure level: 80 dB(A)
- With its 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Durable, lightweight magnesium gear case for extended life and comfort.
- Variable speed trigger for enhanced control and accuracy.
- 1/2" square drive with detent pin for secure socket retention.
- Non-slip gripping surfaces for maximum comfort and control.
- Exclusive reversible battery pack design for optimal tool balance.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- **Supplied in case with 2 batteries and charger.**

FEATURES

Symbol	HD28IW-32C
Wyjście	1/2"
Nm max	440
Częstość uderu [ud/min]	0-2450
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	28
Obroty [obr/min]	0-1450

