PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



Impact wrenches, impact drivers > Impact wrenches



SYMBOL: 4933448545 MANUFACTURER: Milwaukee EAN: 4002395263165 $\star \star \star \star \star$ HD28 IW-502X - 1/2" Impact wrench, 440 Nm, 28 V, 5.0 Ah, HEAVY DUTY, in case, with 2 batteries and charger, 4933448545

link > https://imilwauke.pl/en/20153-hd28-iw-502x-12-impact-wrench-440-nm-28-v-50-ah-heavy-duty-in-case-...

- Voltage: 28 V
- Max. torque: 440 Nm Impact rate: 0-2450 ipm
- No load speed: 0-1450 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 90 min • Weight with battery pack: 4.1 kg

U WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)

Milwaukee



DESCRIPTION

- Vibration screw driving: 11.3 m/s²
- Sound pressure level: 80 dB(A)
- With its 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Durable, lightweight magnesium gear case for extended life and comfort.
 Variable speed trigger for enhanced control and accuracy.
- 1/2" square drive with detent pin for secure socket retention
- · Non-slip gripping surfaces for maximum comfort and control.
- Exclusive reversible battery pack design for optimal tool balance
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 Fuel gauge displays remaining charge.
- REDULTHIUM*-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life. · Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	HD28IW-502X
Wyjście	1/2"
Nm max	440
Częstość udaru [ud/min]	0-2450
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	28
Obroty [obr/min]	0-1450