



SYMBOL: **4933451441** MANUFACTURER: **Milwaukee** EAN: **4002395164004**



M18 CAG125XPD-0X - Angle grinder 125 mm, 18 V, FUEL™, paddle switch, in case, without equipment, 4933451441

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 rpm
- Spindle size: M14
- Paddle switch
- Brake: no
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.5 kg



Product page

link > <https://imilwauke.pl/en/20189-m18-cag125xpd-0x-angle-grinder-125-mm-18-v-fuel-paddle-switch-in-ca...>

DESCRIPTION

- Vibration sanding: 1.4 m/s²
- Vibration at grinding metal: 3.4 m/s²
- Sound power level: 94.2 dB(A)
- Sound pressure level: 83.2 dB(A)
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Premium gearing system - same system as used at high performance corded grinders.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- 100% tool-free wheel change thanks to integrated FIXTEC™ system.
- Slim handle design with paddle switch.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Standard equipment: quick release safety guard, AVS side handle, flange, flange nut, spanner, 2x dust screens.
- **Supplied in case (HD Box) without battery and charger.**

FEATURES

Symbol	M18CAG125XPD-0X
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica tarczy	125.00
Typ włącznika	łopatkowy
Obroty [obr/min]	8500

