



SYMBOL: **4933451544** MANUFACTURER: **Milwaukee** EAN: **4002395145812**



M18 CAG125XPDB-502X - Braking grinder 125 mm, 18V, 5.0Ah, FUEL™, paddle switch, in case with 2 batteries and charger, 4933451544

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 rpm
- Spindle size: M14
- Paddle switch
- Brake: yes
- Braking time: < 2s
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 2.7 kg



WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://milwaukee.pl/en/20193-m18-cag125xpdb-502x-braking-grinder-125-mm-18v-50ah-fuel-paddle-swi...>

DESCRIPTION

- Vibration sanding: 2.15 m/s²
- Vibration at grinding metal: 4.61 m/s²
- Sound power level measured: 89.9 dB(A)
- Sound pressure level: 78.9 dB(A)
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Safety paddle switch with line-lock-out function to prevent automatic start up.
- Premium gearing system - same system as used at high performance corded grinders.
- Slim handle design with paddle switch.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- FIXTEC™ nut for tool-free disc change.
- Anti-vibration side handle for lower vibration.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Standard equipment: quick release safety guard, AVS side handle, flange, FIXTEC nut, 2x dust screens.
- **Supplied in case (HD Box) with 2 batteries and charger.**

FEATURES

Symbol	M18CAG125XPDB-502X
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica tarczy	125.00
Typ włącznika	łopatkowy
Obroty [obr/min]	8500

