



SYMBOL: **4933447799** MANUFACTURER: **Milwaukee** EAN: **4002395006564**



**M12 BPS-421X - Sub compact polisher/sander 76 mm, 12 V, 2.0 and 4.0 Ah, in case, with 2 batteries and charger, 4933447799**

- Voltage: 12 V
- Disc diameter: 76 mm
- No load speed gear 1: 0-2800 rpm
- No load speed gear 2: 0-8300 rpm
- No load speed: 2500/7500 rpm
- Spindle size: M9 x 0.75
- Vibration polishing: 2.95 m/s<sup>2</sup>
- Vibration sanding: 2.3 m/s<sup>2</sup>
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 i 4.0 Ah
- Charger supplied: 80 min
- Weight with battery pack: 1 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~1 759,00 zł~~ **-10%**

**1 583,10 zł** (tax excl.)

(1 947,21 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/20202-m12-bps-421x-sub-compact-polishersander-76-mm-12-v-20-and-40-ah-in-...>

#### DESCRIPTION

- Sound power level: 79.2 dB(A)
- Sound pressure level: 68.24 dB(A)
- Variable 2 speed selection (0-2800/0-8300 RPM) for both polishing and sanding applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Large capacity of 76 mm polishing sponge and 50 mm sanding pad size for fast job completion.
- Long run time allows frequent task completion with one battery charge.
- Compact design with only 130 mm allows access to hard areas.
- Spindle lock allows fast, tool free accessory change.
- Detachable 2 position side handle.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied with polishing pad, sanding pad, polishing sponge white, polishing sponge yellow, lambswool, side handle.
- **Supplied in case (HD Box) with 2 batteries and charger.**

#### FEATURES

Symbol	M12BPS-421X
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica tarczy	76.00
Obroty [obr/min]	2500-7500