



SYMBOL: **4933464618** MANUFACTURER: **Milwaukee** EAN: **4058546225636**



M12 FCOT-0 - Sub compact angle grinder 76 mm, 12 V, FUEL™, without equipment

- Voltage: 12 V
- Disc diameter: 76 mm
- Bore size: 10 mm
- Max. cutting depth: 16.3 mm
- No load speed: 20000 rpm
- Anti-kickback protection: no
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 029,00 zł~~ **-20%**

823,20 zł (tax excl.)

(1 012,54 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/20204-m12-fcot-0-sub-compact-angle-grinder-76-mm-12-v-fuel-without-equipm...>

DESCRIPTION

- Fast accurate cutting with up to 20000 RPM.
- Optimised ergonomic design for best control and one-handed use.
- Only 1.1 kg and 226 mm in length.
- Multi-material cutting capability with variety of blades available (metal cut-off wheel, carbide abrasive blade and diamond tile blade).
- A very capable problem solving tool for cutting steel, stainless steel, non-ferrous materials, drywall, fibre cement, plastic and ceramics.
- Easily adjustable guard and unique forward/reverse selectable blade rotation direction to protect user from debris in various cutting positions.
- Quick release dust shoe with depth adjustment and optional dust extraction port.
- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 76 mm blade offers up to 16.3 mm depth of cut.
- Fuel gauge displays remaining charge.
- Brightest LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Standard equipment: diamond tile blade, carbide abrasive blade, metal cut-off wheel, adjustable dust shoe.
- **Supplied without battery and charger.**

FEATURES

Symbol	M12FCOT-0
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica tarczy	76.00
Typ włącznika	łopatkowy
Obroty [obr/min]	20000