




SYMBOL: **4933403206** MANUFACTURER: **Milwaukee** EAN: **4002395233786**



AG 9-125 XE - Angle grinder 125 mm, 850 W, slide switch, 4933403206

- Power input: 850 W
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 2700-10000 rpm
- Spindle size: M14
- Slide switch
- Brake: no
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: no
- Variable speed: yes
- AVS Anti-Vibration System: no
- Weight: 1.8 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



919,00 zł **-10%**

827,10 zł (tax excl.)

(1 017,33 zł (tax incl.))

PayU  

Product page

link > <https://imilwauke.pl/en/20229-ag-9-125-xe-angle-grinder-125-mm-850-w-slide-switch-4933403206.html>

DESCRIPTION

- Sound power level: 100 dB(A)
- Sound pressure level: 89 dB(A)
- Vibration sanding : 3,5 m/s²
- Vibration at grinding metal: 10 m/s²
- Powerful, 850 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Light weight, slim and compact: a versatile all-purpose angle grinder.
- New digital electronic pack offers constant speed, soft start, motor overload protection and no-load speed limitation.
- Flat metal gear head for excellent visibility of work piece and optimised cutting depth.
- Die-cast magnesium alloy gear case.
- Dust protected bearings and switch.
- Effective cooling fan keeps the motor cool even under heavy duty conditions.
- FIXTEC™ nut for fast and easy disc change.
- Burst resistant quick release safety guard for easy adjustment.
- Automatic cut-off carbon brushes.
- 4 m rubber cable.
- Standard equipment: quick release safety guard, side handle, flange, FIXTEC™ flange nut, 4 m cable.

FEATURES

Symbol	AG9-125XE
Moc [W]	850
Zasilanie	network
Średnica tarczy	125.00
Typ włącznika	suwakowy
Obroty [obr/min]	2700-10000