
PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



FAN: 4002395004959



MANUFACTURER: Milwaukee $\star \star \star \star \star$ M18 CCS55-0 - Circular saw for wood and plastics 55 mm, 18 V, FUEL™, without equipment, 4933446223

NOTE: The product has been withdrawn from sale by the manufacturer. No suggested replacements available.

- Voltage: 18 V
- No load speed: 5000 rpm
- Blade diameter: 165 mm
- Bore size: 15.87 mm

SYMBOL: 4933446223

- Max.cutting depth 90°: 55 mm
- Max. cutting depth 45°: 41 mm
- Sound power level: 91.8 db(A)



link > https://imilwauke.pl/en/20288-m18-ccs55-0-circular-saw-for-wood-and-plastics-55-mm-18-v-fuel-with...



DESCRIPTION

- Sound pressure level: 80.8 dB(A)
- Vibration level: 2.45 m/s²
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight: 2.8 kg

• Brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge.

- REDLINK PLUS[™] intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load. REDLITHIUM[™]-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance
- · Magnesium shoe reduces weight and maximises durability.
- Integrated dust blower keeps cut line clear.
- Hang hook allows safe storage of the tool.
 Integrated battery fuel gauge & LED light.
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries.
 Standard equipment: circular saw blade, side fence.
- · Supplied without battery and charger.

FEATURES

Symbol	M18CCS55-0
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica tarczy	165.00
Obroty [obr/min]	5000