



SYMBOL: **4933448235** MANUFACTURER: **Milwaukee** EAN: **4002395262816**



M12 CCS44-402C - Sub compact circular saw 44 mm, 12 V, 4,0 Ah, FUEL™, with 2 batteries and charger, 4933448235

- Voltage: 12 V
- No load speed: 3600 rpm
- Blade diameter: 140 mm
- Bore size: 20 mm
- Max. cutting depth 90°: 44 mm
- Max. cutting depth 45°: 33 mm
- Sound pressure level : 82 dB(A)
- Sound power level measured: 93 db(A)
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 4.0 Ah
- Charger supplied: 80 min
- Weight with battery pack: 2.7 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/20298-m12-ccs44-402c-sub-compact-circular-saw-44-mm-12-v-40-ah-fuel-with-...>

DESCRIPTION

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 2x more cuts per charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance.
- Magnesium shoe reduces weight and maximises durability.
- Integrated dust blower keeps cut line clear.
- LED light illuminates the cut line.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Standard equipment: circular saw blade, side fence.
- Supplied in case Kitbox with 2 batteries and charger.

FEATURES

Symbol	M12CCS44-402C
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica tarczy	140.00
Obroty [obr/min]	3600

