



SYMBOL: **4933419022** MANUFACTURER: **Milwaukee** EAN: **4.0024E+12**



## HD28 CS-0 - Circular saw 54 mm, 28 V, HEAVY DUTY, without equipment, 4933419022

- Voltage: 28 V
- Prędkość bez obciążenia: 4200 rpm
- Max. cutting depth 90°: 54 mm
- Max. cutting depth 45°: 39 mm
- Blade diameter: 165 mm
- Arbor size: 15.87 mm
- Sound power level: 102 dB(A)
- Sound pressure level: 91 dB(A)
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight: 2.7 kg
- Weight with battery pack: 3.6 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page

link > <https://imilwauke.pl/en/20300-hd28-cs-0-circular-saw-54-mm-28-v-heavy-duty-without-equipment-4933...>

### DESCRIPTION

- Powerful 4200 rpm motor easily cuts most timber construction materials.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Versatile 54 mm cutting depth, 50° bevel cut capacity.
- Heavy Duty construction with all metal lower / upper blade guards and aluminium shoe.
- Left-blade design for optimal cut-line visibility and control.
- Electronic motor brake, saw blade stops within seconds.
- Ergonomic soft grip handle design for more comfortable use.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Supplied with 24 tooth saw blade, parallel guide, dust port and allen key.
- **Supplied without battery and charger.**

### FEATURES

Symbol	HD28CS-0
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	28
Średnica tarczy	165.00
Obroty [obr/min]	4200

