



SYMBOL: **4933451378** MANUFACTURER: **Milwaukee** EAN: **4.0024E+12**



M18 CSX-502X - Reciprocating saw 18 V, 5.0 Ah, SAWZALL™, FUEL™, in case with 2 batteries and charger, 4933451378

- Voltage: 18 V
- Stroke length: 28.6 mm
- No load stroke rate: 0 - 3000 spm
- Max. cutting depth in soft-wood: 300 mm
- Max. cutting depth in steel and aluminium: 20/25 mm
- Max. cutting depth in non-ferrous metal: 25 mm
- Max. cutting depth in metal pipe: 150 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Weight with battery pack: 4.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/20322-m18-csx-502x-reciprocating-saw-18-v-5-0-ah-sawzall-fuel-in-case-with...>



DESCRIPTION

- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Vibration cutting : 16.7 m/s²
- Vibration cutting wooden beam: 22.3 m/s²
- Sound power and pressure level: 95.9 / 84.9 dB(A)
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- FIXTEC™ blade clamp for fast and easy blade changes without any key.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge & LED light.
- Durable metal rafter hang hook for work space management and safety.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Standard equipment: 1 SAWZALL™ blade.
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M18CSX-502X
Długość skoku	28.60
Ilość akumulatorów	2
Ilość suwów	0-3000
Zasilanie	battery
Napięcie akumulatora [V]	18

