





SYMBOL: 4933451665

MANUFACTURER: Milwaukee

FAN: 4.0024E+12

\*\*\*\*

M18 ONESX-0 - Reciprocating saw 18 V, SAWZALL®, ONE-KEY™, without equipment, 4933451665

- · Voltage: 18 V
- Stroke length: 28.6 mm
- No load stroke rate: 0 3000 spm
- Max. cutting depth in soft-wood: 300 mm
- Max. cutting depth in steel and aluminium: 20/25 mm
- Max. cutting depth in non-ferrous metal: 25 mm
- Max. cutting depth in metal pipe: 150 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 4/4.3 kg



link > https://imilwauke.pl/en/20328-m18-onesx-0-reciprocating-saw-18-v-sawzall-one-key-without-equipmen... > https://imilwauke.pl/en/20328-m18-one-key-without-equipmen... > https://imilwauke.pl/en/20328-m18-one-key-without-equipmen...









## DESCRIPTION

- M18 CSX but with ONE-KEY™ technology.
- Connect via Bluetooth® with the ONE-KEY™ app.
  ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- Custom cut control provides advanced control over cutting speeds.
- · Adjustable soft start provides more accurate cut-starts in various materials minimising blade chatter and assisting in cleaner faster cuts
- Cut optimisation gives longer blade life and easier cutting in a wide range of materials.
- Automatic brake allows the saw to stop the blade after it breaks through a material preventing accidental cuts in adjacent materials.
  Plunge cut allows the blade to penetrate the material at a slower speed and then automatically ramp to full speed, sensing an increase in force from the user.
- Save up to four custom settings to the tools memory allowing fast and easy selection of the most used configurations.
  ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Flexible battery system: works with all MILWAUKEE® M18™ <u>batteries</u>. Standard equipment: SAWZALL™ blade.
- · Supplied without battery and charger.

## FEATURES

. 2.1.0.1.20	
Symbol	M180NESX-0
Długość skoku	28.60
Ilość akumulatorów	brak
Ilość suwów	0-3000
Zasilanie	battery
Napięcie akumulatora [V]	18

